

AXIS P1447-LE

Fully-featured, all-around 5 MP surveillance

AXIS P1447-LE Network Camera is a cost-effective, all-around camera providing excellent image quality at full frame rate in 5 megapixel resolution and in 16:9 format. Fully-featured with Lightfinder, OptimizedIR and Forensic WDR, forensic details are captured even in challenging light conditions including low light and strong backlight. Outdoor-ready with a wide temperature range, this sturdy and impact resistant camera has shock detection and is ready for extreme temperatures. AXIS P1447-LE offers easy installation with remote zoom and focus for fine tuning of the picture. With Axis Zipstream, I/O and audio support, AXIS P1447-LE got you covered.

- > 5 megapixel resolution in full frame rate
- > Ease of installation
- > Forensic WDR, Lightfinder, and OptimizedIR
- > I/O and audio support
- > Axis Zipstream technology



AXIS P1447-LE

Camera		Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, external output activation, day/night mode
Image sensor	1/2.9" progressive scan RGB CMOS	
Lens	2.8–8.5 mm, F1.2 Horizontal field of view 104°–36° Vertical field of view 55°–20° Varifocal, Remote focus and zoom, P-Iris control, IR corrected	
Day and night	Automatically removable infrared-cut filter	Data streaming Event data
Minimum illumination	Color: 0.15 lux, at 50 IRE F1.2 B/W: 0.03 lux, at 50 IRE F1.2 0 lux with IR illumination on	
Shutter time	1/62500 s to 2 s	
Video		Built-in installation aids Pixel counter, remote zoom (3x optical), remote focus, auto rotation
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	
Resolution	3072x1728 to 160x90	
Frame rate	Up to 25/30 fps (50/60 Hz) in all resolutions	General
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	
Multi-view streaming	Up to 8 individually cropped out view areas	
Image settings	Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, exposure mode, exposure zones, compression, orientation: auto, 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, dynamic text and image overlay, privacy masks	Casing IP66/IP67-, NEMA 4X-, and IK10-rated casing Polycarbonate blend and aluminium Color: white NCS S 1002-B
Pan/Tilt/Zoom	Digital PTZ	
Audio		
Audio streaming	Audio in, simplex	Sustainability PVC free
Audio compression	24bit LPCM, AAC-LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate	
Audio input/output	External microphone input or line input	
Network		Memory 1024 MB RAM, 512 MB Flash
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, digest authentication, user access log, centralized certificate management	
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP ^a , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP	
System integration		Power Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Typical: 6.7 W, max 12.95 W
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at <i>axis.com</i> AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile S and ONVIF [®] Profile G, specification at <i>onvif.org</i>	
Analytics	Included AXIS Video Motion Detection Supported AXIS Digital Autotracking, AXIS Perimeter Defender, AXIS Cross Line Detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see <i>axis.com/acap</i>	
Event triggers	Analytics Detectors: live stream accessed, video motion detection, audio detection, day/night mode, shock detection, tampering Hardware: network, temperature Input Signal: digital input port, manual trigger, virtual inputs Storage: disruption, recording System: system ready Time: recurrence, use schedule	Connectors RJ45 10BASE-T/100BASE-TX PoE 3.5 mm mic/line in I/O: 4-pin terminal block for 1 alarm input and 1 output
Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email	
		IR illumination Optimized IR with power-efficient, long-life 850 nm IR LEDs Range of reach 30 m (98 FT) or more depending on the scene
		Storage Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <i>axis.com</i>
		Operating conditions -40 °C to 60 °C (-40 °F to 140 °F) Humidity 10–100% RH (condensing)
		Storage conditions -40 °C to 65 °C (-40 °F to 149 °F)
		Approvals EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66/IP67, IEC/EN 62262 IK10, NEMA 250 Type 4X, NEMA TS-2-2003 v02.06 Other IEC 62471
		Weight With weather shield: 1 KG (2.2 lb)
		Dimensions Ø132 x 260 mm (Ø5 3/16 x 10 1/4 in)
		Included accessories Installation guide, Windows [®] decoder 1-user license, drill hole template, connector kit, mounting bracket AXIS Weather Shield L
		Optional accessories AXIS T94F01M J-Box/Gang Box Plate AXIS T91A47 Pole Mount AXIS T94P01B Corner Bracket AXIS T94F01P Conduit Back Box AXIS Weather Shield K Axis PoE Midspans For more accessories, see <i>axis.com</i>
		Video management software AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available on <i>axis.com/vms</i>
		Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
		Warranty Axis 3-year warranty and AXIS Extended Warranty option, see <i>axis.com/warranty</i>

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).

Environmental responsibility:

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).

Environmental responsibility:

www.axis.com/environmental-responsibility